


**Product specifikation 200-14**

|                                    |                                |                                |                     |                             |             |
|------------------------------------|--------------------------------|--------------------------------|---------------------|-----------------------------|-------------|
| Utfärdad av<br>Anna<br>Hammarstedt | Godkänd av<br>Anna Hammarstedt | Verifierad av<br>Anette Alrutz | Datum<br>2017-05-08 | Dokument nr.<br>PS-200-14-1 | Utgåva<br>3 |
|------------------------------------|--------------------------------|--------------------------------|---------------------|-----------------------------|-------------|

|                                 |                                                                                                                                                                                           |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Product:                        | 14-200                                                                                                                                                                                    |  |
| Article number:                 | Please contact our sales department.                                                                                                                                                      |                                                                                     |
| Product Description:            | 14mm closure for vial with flexible ring seal adapted for GL14-thread.                                                                                                                    |                                                                                     |
| <b>Technical specifications</b> |                                                                                                                                                                                           |                                                                                     |
| Drawings:                       | Product drawing: S 14-200<br>Neck drawing: H 200                                                                                                                                          |                                                                                     |
| Sealing:                        | Flexible ring seal                                                                                                                                                                        |                                                                                     |
| Plastic resin:                  | PPH                                                                                                                                                                                       |                                                                                     |
| Master batch:                   | Please contact our sales department.                                                                                                                                                      |                                                                                     |
| Injection moulding:             | ISO 14644-1 class 8                                                                                                                                                                       |                                                                                     |
| Recommended Capping torque:     | 0,7 Nm                                                                                                                                                                                    |                                                                                     |
| Storage durability:             | 2 year, keep room temperatured in tightly sealed cardboard boxes.                                                                                                                         |                                                                                     |
| <b>Quality Control</b>          |                                                                                                                                                                                           |                                                                                     |
| Standards and norms             | SS-EN ISO 9001, SS- EN ISO 14001, FSSC 22000<br>Sampling procedure: SS 020130-ISO2859 normal 1<br>Defect classes according to KP-002                                                      |                                                                                     |
| <b>Delivery</b>                 |                                                                                                                                                                                           |                                                                                     |
| Packaging                       | 1000 pcs packed in plastic bag, closed by welding. 9 bags packed in cardboard boxes 45dm <sup>3</sup> . Labels on the boxes. 24 boxes on each pallet with shrinked foil wrapped around.   |                                                                                     |
| Traceability                    | Marking for traceability contains EVP article number, customer article number, production order number, pieces per carton, EVP order number customer order number and date and signature. |                                                                                     |